



SM-210 Monocrystalline Solar Panel

Product Description

SM-210 Monocrystalline Solar Panels have the highest efficiency rates since they are made out of the highest-grade silicon. The efficiency rates of these solar panels are typically 15-20%, which up to four times the amount of electricity as thin-film solar panels. Since these SM-210 Monocrystalline Solar Panels yield the highest power outputs, they require the least amount of space compared to any other types. What's more, SM-210 Monocrystalline Solar Panels live the longest and will save lot of your time to replace it. Also, it tend to perform better than similarly rated polycrystalline solar panels at low-light conditions.

Features:

- High conversion efficiency.
- Low power tolerance of 0~+3%.
- Low degradation under light exposure.
- Can withstand high wind-pressure, snow load and extreme temperature.
- Passing IEC61215 2400Pa mechanical load test.

Benefits of Monocrystalline Solar Panel:

• Monocrystalline Solar Panels have the highest efficiency rates since they are made out of the highest-grade silicon. The efficiency rates of Monocrystalline Solar Panels are typically 15-20%. Monocrystalline Solar Panels produce up to four times the amount of electricity as



Zhejiang Seming Electronic Co., Ltd

thin-film solar panels.

- Monocrystalline Solar Panels are space-efficient. Since these solar panels yield the highest power outputs, they also require the least amount of space compared to any other types.
- Monocrystalline Solar Panels live the longest. Most solar panel manufacturers put a 25-year warranty on their Monocrystalline Solar Panels.
- Tend to perform better than similarly rated poly panels at low-light conditions.

Detailed Parameters:

Model Type	SM-210
Dimensions	1580*808*35
Peak Power(Pmax)	210
Maximum Power Voltage(Vmp)	38.76
Maximum Power Current(Imp)	5.42
Open Circuit Voltage(Voc)	45.98
Short Circuit Current(Isc)	5.80
Cells Efficiency(%)	19.40
Module Efficiency(%)	16.45
Maximum System Voltage(V)	1000
Maximum Series Fuse Rating(A)	15
Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.450%

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: sales@seminglighting.com**



Zhejiang Seming Electronic Co., Ltd


Voc Temperature Coefficients(V/°C)	-0.350%
Lsc Temperature Coefficients(A/°C)	+0.040%
NOCT Nominal Operating Cell Temperature(°C)	47±2
Operating and Storage Temperature(°C)	-40~+85
Standard Test Conditions(STC)	1000W/m ² , AM1.5; 25+/-2°C
Warranty on product materials and processing	10 years
Power output warranty	10years:90%,25years:85%
Certifications	TUV、CE、CQC、UL
Products Certifications	IEC61215、IEC61730、MCS CEC
Factory Certifications	ISO9001:2008、ISO14001、ISO18001

Product Display:

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: sales@seminglighting.com**



Zhejiang Seming Electronic Co., Ltd



210W 36V Mono Panel



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: sales@seminglighting.com**



Zhejiang Seming Electronic Co., Ltd



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: sales@seminglighting.com**



Application:

- On-grid residential roof-tops.
- On-grid commercial/industrial roof-tops
- Solar power plants
- Off-grid system
- Other on-grid applications