



## SM-FL1A LED Flood Light

### Product Description

SM-FL1A LED Flood Lights are broad-beamed, high-intensity artificial lights. They are often used to illuminate outdoor playing fields while an outdoor sports event is being held during low-light conditions. The white beam of light produced by it is very much similar to daylight. When SM-FL1A LED Flood Lights be used in stadiums, it makes the spectators feel as though it is day time. Also, SM-FL1A LED Flood Lights are impervious to temperature fluctuations and environmental conditions. Unlike some other lights, LEDs remain stable and functional even in freezing conditions. This makes them all the more ideal for cold warehouses and storage areas.

Being free of Mercury, Lead and Carbon Emissions, SM-FL1A LED Flood Lights do not give out any harmful emissions such as carbon. As a result, they are much friendlier to the environment and also to the health of people nearby. What's more, SM-FL1A LED Flood Lights do not emanate heat and conserve the maximum amount of electricity, which also leads to longevity and safety.

For these advantages of SM-FL1A LED Flood Lights, these lights are ideal for use in cold storage warehouses, or used as a stage lighting instrument in live performances such as concerts and plays. In the top tiers of many professional sports, it is a requirement for stadiums to have floodlights to allow games to be scheduled outside daylight hours.

### Features

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp: +8618267537265; Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



# Zhejiang Seming Electronic Co., Ltd

1. Modular pluggable technology, easy tool onsite maintenance,
2. Honeycomb and whole structure cooling technology, high efficient heat dissipation,
3. Double-coupling IP68 protection, highest waterproof level,
4. Intelligent constant current driving technology, long life span,
5. Ergonomic light distribution to achieve uniform illuminating effect,
6. Free modular serialization and full power range solutions

## Detailed Parameters

Input Voltage	Power Efficiency	Power Factor	Junction Temperature	CRI	Working Environment	Storage Temperature			
AC100V-277V	91%	0.95	<80°C	Ra ≥ 70	-40°C~+50°C 10%~90%RH	-40 °C ~+50°C			
LED Life span	Surge Protection	CCT	LED Brand	Material	IP Rating				
>60000Hours	10KV/5KA	3000K, 4000K, 5000K, 5700K	Lumileds	Metal	LED Module IP68, Power Supply IP67				
Model	System	LM/W (Ultra	LM/W (High)	Initial Lumens	Initial Lumens	Product Size	Packaging dimension	N.W. (Kg)	G. W.(

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp: +8618267537265**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



# Zhejiang Seming Electronic Co., Ltd

	Power( W)	High)		(Ultra High)	(High)	(mm)	(mm)		Kg)
FL1A-1	40	155	115	6200	4600	350*33 0*335	450*430* 230	4.8	5.9
	50	150	110	7500	5500	350*33 0*335	450*430* 230	4.8	5.9
	60	145	105	8700	6300	350*33 0*335	450*430* 230	4.8	5.9
FL1A-2	80	160	120	12800	9600	430*33 0*335	520*430* 230	6.4	7.9
	100	155	115	15500	11500	430*33 0*335	520*430* 230	6.4	7.9
	120	150	110	18000	13200	430*33 0*335	520*430* 230	6.4	7.9
FL1A-3	120	160	120	19200	14400	510*33 0*335	600*430* 230	7.4	8.9
	150	155	115	23250	17250	510*33 0*335	600*430* 230	7.4	8.9
	180	150	110	27000	19800	510*33 0*335	600*430* 230	7.4	8.9
FL1A-4	160	160	120	25600	19200	590*33	680*430*	8.3	9.9

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp: +8618267537265; Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



# Zhejiang Seming Electronic Co., Ltd

						0*335	230		
	200	155	115	31000	23000	590*33	680*430*	8.3	9.9
						0*335	230		
	240	150	110	36000	26400	590*33	680*430*	8.3	9.9
						0*335	230		
FL1A-5	200	160	120	32000	24000	670*33	785*430*	11.1	12.
						0*475	230		9
	250	155	115	38750	28750	670*33	785*430*	11.1	12.
						0*475	230		9
	300	150	110	45000	33000	670*33	785*430*	11.1	12.
						0*475	230		9
FL1A-6	240	160	120	38400	28800	750*33	840*430*	12.5	14.
						0*475	230		4
	300	155	115	46500	34500	750*33	840*430*	12.5	14.
						0*475	230		4
	360	150	110	54000	39600	750*33	840*430*	12.5	14.
						0*475	230		4
FL1A-7	280	160	120	44800	33600	830*33	920*430*	13.7	15.
						0*475	230		6
	350	155	115	54250	40250	830*33	920*430*	13.7	15.
						0*475	230		6

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp: +8618267537265**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



## Product Display




Black




Gray




# Zhejiang Seming Electronic Co., Ltd




**T5S3040**  
IESNA Type VS Short




**11D3030**  
Beam Angle (50%) 110×40DEG




**12D1908**  
Beam Angle(50%)12DEG




**25D3725**  
Beam Angle (50%) 25DEG




**40D3540**  
Beam Angle (50%) 40DEG



**60D3560**  
Beam Angle (50%) 60DEG



**90D3590**  
Beam Angle (50%) 90DEG



**00D1010**  
Beam Angle (50%) 110DEG



# Zhejiang Seming Electronic Co., Ltd



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp: +8618267537265**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**