

SM-FL2C LED Flood Light

Product Description

storage areas.

SM-FL2C LED Flood Lights are broad-beamed, high-intensity artificial lights. They are often used to illuminate outdoor playing fields while an outdoor sports event is being held during low-light conditions. The white beam of light produced by it is very much similar to daylight. When SM-FL2C LED Flood Lights be used in stadiums, it makes the spectators feel as though it is day time. Also, SM-FL2C LED Flood Lights are impervious to temperature fluctuations and environmental conditions. Unlike some other lights, LEDs remain stable and functional even in freezing conditions. This makes them all the more ideal for cold warehouses and

Being free of Mercury, Lead and Carbon Emissions, SM-FL2C LED Flood Lights do not give out any harmful emissions such as carbon. As a result, they are much friendlier to the environment and also to the health of people nearby. What's more, SM-FL2C LED Flood Lights do not emanate heat and conserve the maximum amount of electricity, which also leads to longevity and safety.

For these advantages of SM-FL2C LED Flood Lights, these lights are ideal for use in cold storage warehouses, or used as a stage lighting instrument in live performances such as concerts and plays. In the top tiers of many professional sports, it is a requirement for stadiums to have floodlights to allow games to be scheduled outside daylight hours.

Features



- 1. Modular pluggable technology, easy tool onsite maintenance,
- 2. Honeycomb and whole structure cooling technology, high efficient heat dissipation,
- 3. Double-coupling IP68 protection, highest waterproof level,
- 4. Intelligent constant current driving technology, long life span,
- 5. Ergonomic light distribution to achieve uniform illuminating effect,
- 6. Free modular serialization and full power range solutions

Detailed Parameters

Input Voltage	Power	Power Pov		Junction		CRI		Working		Storage	
	Efficiency Fa		Factor	Temperature			Environment		Temperature		
AC100V-	91%		0.95	<80℃		Ra≥70		-40°	C~+50°C	-40	$^{\circ}$
277V								10%	~90%RH	~+50°C	
LED Life span	Surge	Surge Co		LED Bra	nd	Material		IP Rating			
	Protection										
>60000Hours	10KV/5	10KV/5KA 3		3000K, Lumileds		Metal		LED	Module	IP68, P	ower
			4000K,					Sup	ply IP67		
	50		5000K,								
	5700K										
Model	Syste	LM/V	V LM/V	V Initia	I	Initial	Prod	duct	Packaging	N.W.	G.
	m	(Ultra	a (High) Lume	ens	Lumens	Size		dimension	n (Kg)	W.(

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



			8 ~ •	8					
	Power(High)		(Ultra	(High)	(mm)	(mm)		Kg)
	W)			High)					
FL2C-1	40	155	115	6200	4600	360*20	430*265*	3.2	4.1
						0*95	150		
	50	150	110	7500	5500	360*20	430*265*	3.2	4.1
						0*95	150		
	60	145	105	8700	6300	360*20	430*265*	3.2	4.1
						0*95	150		
FL2C-2	80	160	120	12800	9600	360*20	430*265*	4.7	5.7
						0*175	230		
	100	155	115	15500	11500	360*20	430*265*	4.7	5.7
						0*175	230		
	120	150	110	18000	13200	360*20	430*265*	4.7	5.7
						0*175	230		
FL2C-3	120	160	120	19200	14400	360*26	430*335*	5.6	6.6
						0*255	330		
	150	155	115	23250	17250	360*26	430*335*	5.6	6.6
						0*255	330		
	180	150	110	27000	19800	360*26	430*335*	5.6	6.6
						0*255	330		
FL2C-4	160	160	120	25600	19200	360*26	475*430*	6.7	8.0

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



_			8 ~ •				70, 200		
						0*335	210		
	200	155	115	31000	23000	360*26	475*430*	6.7	8.0
						0*335	210		
	240	150	110	36000	26400	360*26	475*430*	6.7	8.0
						0*335	210		
FL2C-5	200	160	120	32000	24000	360*36	615*430*	8.4	9.9
						0*415	210		
	250	155	115	38750	28750	360*36	615*430*	8.4	9.9
						0*415	210		
	300	150	110	45000	33000	360*36	615*430*	8.4	9.9
						0*415	210		
FL2C-6	240	160	120	38400	28800	360*36	660*430*	9.4	11.
						0*495	210		1
	300	155	115	46500	34500	360*36	660*430*	9.4	11.
						0*495	210		1
	360	150	110	54000	39600	360*36	660*430*	9.4	11.
						0*495	210		1
FL2C-7	280	160	120	44800	33600	360*36	695*430*	10.1	11.
						0*575	210		6
	350	155	115	54250	40250	360*36	695*430*	10.1	11.
						0*575	210		6

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



							· · · · · · · · · · · · · · · · · · ·		
	420	150	110	63000	46200	360*36	695*430*	10.1	11.
						0*575	210		6
FL2C-8	320	160	120	51200	38400	360*36	785*430*	13.1	14.
						0*655	230		8
	400	155	115	62000	46000	360*36	785*430*	13.1	14.
						0*655	230		8
	480	150	110	72000	52800	360*36	785*430*	13.1	14.
						0*655	230		8

Product Display









