

V5 LED Street Light

Product Description

The complexities of transportation infrastructure mean varying types of illumination are needed to ensure traffic flows smoothly, people feel safe, and cities save on costs. V5 LED Street light is a cost-effective and sustainable choice for cities today for it can reduce energy use by up to 70% with LED lighting technology, and remote management lowers maintenance costs because of its outstanding working ability against harsh environments such as strong wind, low temperature, and so on. Also, it reduce CO2 emissions for a greener, more sustainable city.

V5 LED Street light Features

- 1. Modular design, full power free combination, simple tool maintenance.
- 2. Honeycomb type heat dissipation and full structure heat dissipation technology, high performance heat dissipation.
- 3. The original high efficiency Lumileds LED chip, single light damage will not affect the whole light.
- 4. The longitudinal uniformity 0.95, more comfortable and safety for driver.
- 5.Intelligent constant current driver, over temperature, over voltage, over current protection, ensure product stability.
- 6. 10KV lightning protection design, to protect the product from the induction and conduction of lightning damage.



- 7. Support PWM dimming, timing dimming, support 0-10V dimming interface.
- 8. Water proof of IP68, avoid water vapor or corrosive gas erosion of chips and circuit boards.
- 9.AC90-305V, suitable for many countries.

Detailed Parameters


Model	V5-1	V5-2	V5-3
Power	30W	60W	40W-60W
Light	36pcs	72pcs	40-64pcs
Source			
Luminous	>3900 lm	>7800 lm	>4600 lm~>6600 lm
Chip	LUMINLEDS/OSRAM		
Brand			
Driver	Donlim/ACHV		
Brand			
Input	100-277V~50/60Hz		
Voltage			
ССТ	3000K-5700K		
Luminous	130 lm/w		
Efficiency			
CRI	>Ra70		

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com




_	2 Znejlang Seming Electronic Con, Eta
PF	>0.95
Total	<15%
harmonic	
distortion	
IP Rating	lp67
Working	-20°C~+50°C
Temperat	
ure	
Wind	12
Proof	
Index	
Working	>50000h
time	
Pole	60mm
interface	

Product Display



cd/klm — CO-C180, 148. 4度 — C90-C270, 90. 6度









Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com





Application

Expressway, park, village, mine, wharf, factory





Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



